Signature: Owner / Agent



BACKFLOW PREVENTION ASSEMBLY TEST MAINTENANCE REPORT

Account N	No. :	Manufacturer :		Size :			
Meter N	No. :			Serial Number :			
Service Addre	ess:			_ Cage □		Alarmed	
Meter Read :	Prop	Proper Installation: (Y/N) Detector Flow: (Y/N) Inlet Water F			Pressure :	PSI	
Assembly: RP DC PVB DCDA RPDA RPDA-II RPDA-II	REDUCED PRESSURE PRINCIPLE ASSEMBLY			PRESSURE VACUUM BREAKER			
	DOUBLE CHECK ASSEMBLY					B) (E) WE	
	Check Valve #1	Check Valve #2	Relief '	Relief Valve		Air Inlet	
Initial Test	☐ Tight ☐ Leaked Holdin PSID:	☐ Tight ☐ Leaked Holding PSID:	☐ Discharging	☐ Did Not Open ☐ Discharging Opening PSID:		☐ Did Not Open ☐ Discharging Opening PSID:	
R E P	☐ Cleaned	☐ Cleaned	☐ Cleaned	☐ Cleaned ☐ Replaced ☐ Rubber Repair Kit ☐ Other		Check Valve	
	☐ Replaced☐ Rubber Repair Kit	☐ Replaced ☐ Rubber Repair Kit				Holding PSID:	
A I R S	□ Other	☐ Other ————————————————————————————————————	□ Other			☐ Cleaned☐ Replaced☐ Rubber Repair Kit	
	When existing backflow as	sembly is replaced, complet	e this block and "Final T	est" with new a	ssembly informat	ion:	
Final Read:	Size:	Manufacturer: Model:		Serial No.:			
Final Test	☐ Closed Tight Holding PSID:	□ Closed Tight Holding PSID:			D:		
Comments:	<u>l</u>		L				
TEST RESULTS -	I certify the above to be true and cor	rect.					
Initial	Date: Cert. #:	Tested by (print name) : Signature:				□ Passed □ Failed	
Repair	Date:	Repaired by :					
Final	Date: Retested by (print name) :					□ Passed □ Failed	

ASSEMBLY FAILURE OR CUSTOMER'S FAILURE TO TEST: In accordance with the State and Local Laws, the assembly shall be repaired or replaced within 15 days of failure. Failure of the customer to complete assembly testing and submit report(s) within the stipulated time frame shall result in the discontinuance of water service.